

# ROM - COMPACT

HP sewer jetting skid-mounted unit

**ROM**  
KOKS GROUP



# ROM COMPACT

The ROM COMPACT is the ideal high pressure sewer jetting skid-mounted unit for the unblocking and cleaning of lateral and main lines up to Ø 300mm in the sanitary sewer system.

Thanks to its compact and light-weight design (from 210kg), the unit is suitable for light to medium-weight commercial vehicles.

The ROM COMPACT is designed according to a completely new concept. Furthermore, the modernised machine has a totally new design. For these reasons the ROM COMPACT is considered among the first of a new generation of sewer jetting machines. Special attention has been given to both the functionality and the design of the machine. The carefully thought out array of optional equipment makes the price/quality relationship even more attractive for both starting and professional sewer jetting specialists.



## TYPICAL ROM COMPACT CHARACTERISTICS

### COST SAVING

The ROM COMPACT is light (from 210kg), which makes it suitable for light- to mediumweight commercial vehicles, such as the VW Transporter and the MB Vito. The COMPACT is available in both petrol and diesel engine configurations. The diesel engine ensures low fuel consumption and therefore a lower hourly usage cost.

### COMPACT DESIGN

The design of the ROM COMPACT is extremely compact. The frame shot blasted, primed and finished with a durable powder coating in the colour red (RAL 3002). The ROM COMPACT is standard equipped with an attractive control panel including

a control cabinet with push buttons. There are drip pans under both reels.

### MAINTENANCE-FRIENDLY

The ROM COMPACT is a maintenance-friendly machine. Due to solid motor/pump combinations of the B&S and Kubota engines and SPECK high-pressure pumps, the machine requires very little service. Besides this, the ROM COMPACT provides easy access for service of the machine. It includes a new-generation, impactresistant water filter with a quick-stop.

### CE-MARK

The ROM COMPACT is built by professionals at an ISO-certified company and finished to your specifications. Also, the ROM COMPACT is produced in compliance with the safety requirements demanded for the CE mark of quality.



# Quality you expect at a price you won't



The ROM COMPACT is available in the following configurations:

Article number	0250	0251	0254	0255
Name	ROM COMPACT Base 190/30	ROM COMPACT 150/40	ROM COMPACT 140/50	ROM COMPACT 140/45 Diesel
Engine	13,2kW / 18hp B&S VANGUARD Petrol engine		16,2kW / 22hp B&S VANGUARD Petrol engine	12,5kW / 17hp Kubota Z 602 Diesel
Pump	Speck 190 bar - 30 l/min	Speck 150 bar - 40 l/min	Speck 140 bar - 50 l/min	Speck 140 bar - 45 l/min
Tank capacity	400l			
Empty weight	approx. 210kg	approx. 225kg	approx. 230kg	approx. 275kg
Dimensions (l x w x h)	1050 x 1190 x 1100mm.			
HP sewer jetting hose	50m. 3/8" (ND10)		50m. 1/2" (ND13)	



Front view ROM COMPACT Base 190/30  
Petrol engine



Front view ROM COMPACT 140/50  
Petrol engine



Front view ROM COMPACT 140/45 Diesel version  
(with a different control panel, heat exchanger, fuel filter etc.)



Drip pan prevents dirt



Userfriendly water-repellent control panel



Compact and lightweight, suitable for light- to mediumweight commercial vehicles

# Options

**ROM**  
KOKS GROUP



Remote control Easy-Remote  
(6-channel)



Filling hose reel



Hydraulically driven HP reel, incl.  
extendable hose guide with bearings



80m. 1/2" (ND13) sewer-jetting hose  
instead of 50m.



STORZ coupling



Working light with magnetic bracket

- Radiographic remote control type 'Easy-Remote' 6-channel incl. speed regulation (petrol versions)
- Radiographic remote control type Professional Yellow 7- or 11-channel incl. speed regulation (diesel versions)
- Extra cable reel with 50m. cable at radiographic remote control
- Cable remote control system with electric 3-way switching and speed regulation
- Working light with magnetic bracket
- Fan incl. installation on roof
- Filling hose reel
- Hydraulically driven HP reel, incl. speed regulation and extendable hose guide with bearings. The engine is safely and indiscernibly integrated in the core of the reel
- 2nd HP reel (not in combination with filling hose reel)
- 40m. 3/8" HP hose on 2nd HP reel
- STORZ coupling with filter on the water tank
- Dry run protection
- Digital hour and revolution counter
- ROM Pulsation system
- 80m. 1/2" (ND13) sewer jetting hose instead of 50m.
- Fixed venturi-type ejector on the water tank
- Spray gun with lance and flat-spray nozzle
- Hot water unit, complete package integrated on machine
- Extra water tank

## ROM bv

Harselaarseweg 63  
3771 MA Barneveld, Holland

Tel : +31 (0)342 49 04 17  
Fax : +31 (0)342 49 28 00

E-mail : [info@rombv.com](mailto:info@rombv.com)  
Internet : [www.rombv.com](http://www.rombv.com)

