

# ROM 900 SEWER JETTING TRAILER

**ROM**  
KOKS GROUP



# ROM 900

The new ROM 900 sewer cleaning trailer. Stylish design, superior userfriendliness. Its attractive design and exceptionally complete range of equipment make the new ROM 900 distinct from all other sewer cleaning trailers.

The ROM 900 is fitted with a number of features as standard, including:

- 270° rotational HP reel with hydraulic drive lockable at any angle)
- Swing-out control panel
- Rotating stainless steel drip tray (prevents the machine from becoming dirty)
- Advanced noise damping package
- Heat exchanger and fuel gauge

The professional ROM 900 is suitable for the unblocking and cleaning lateral lines and main lines in the sanitary sewer system of up to Ø 500mm. Besides the extremely extensive basic version, you can now select a wide range of options and accessories. The ROM 900 trailer can easily be converted for oil spillage control and drainage cleaning.



## TYPICAL ROM 900 FEATURES

### DESIGN

The design is brought to an even higher (European) standard. The new ROM 900 combines attractive design with optimum ease of operation. The low centre of gravity ensures unprecedented stable and safe road holding, both with empty or full water tank. The sophisticated frame ensures a very low dryweight. The innovative design also has a very low drag coefficient (fuel saving).

### OPTIMUM EFFICIENCY

A radial swivel joint, designed in-house, ensures maximum efficiency at the end of the sewer jetting hose.

### TOOLBOXES

There are two large, lockable and rain-resistant toolboxes on either side of the trailer.

### USERFRIENDLY

The new ROM 900 has a handy open storage compartment for your hoses. The machine is also fitted with a 270° rotating high pressure reel with a range of 1m. outside the trailer. The reels have been positioned at the optimum working height on the basis of European research. The control panel and the stainless steel drip tray always rotate along with the hydraulically operated HP reel. An important advantage is that you can use the HP reel both in its resting or extended position.

### EXTENSIVE CHOICE OF THE CONTENTS OF THE WATER TANK

The water tank is excellently protected because it is integrated into the trailer. The overflow can be adjusted as desired, depending on the maximum trailer weight of the vehicle. This gives you an unrestricted choice of 500 up to 900 litres effective watertank capacity.

### DURABLE

The new ROM 900 is extremely durable and low-maintenance. Features such as a hot dip galvanised frame / chassis and the double insulated stainless steel damper will leave you in no doubt about this. The covers and bottom panels are made of flexible impact-resistant material. The large opening angle of the bonnet makes it easy and simple to access components for service and maintenance.

### NOISE INSULATED

The ROM 900 is fitted with an advanced noise-insulation package as standard (72dB). This prevents complaints from people in the vicinity and ensures that you can conduct your work comfortably and with pleasure.



# DESIGN & USERFRIENDLY



The ROM 900 is available in the following versions:

Article number	02290	02292	02294	02296	02298
Model	ROM 900 150/60	ROM 900 200/60	ROM 900 150/75	ROM 900 200/72	ROM 900 150/100
Engine	18kW / 25hp Kubota Diesel	23kW / 32hp Kubota Turbo Diesel		33kW / 45hp Kubota Turbo Diesel	
Pump	Speck 150 bar - 60 l/min	Speck 200 bar - 60 l/min	Speck 150 bar - 75 l/min	Speck 200 bar - 72 l/min	Speck 150 bar - 100 l/min
Tankcapacity	900l				
Empty weight	approx. 950kg	approx. 975kg		approx. 1025kg	
Dimensions l x w x h	4150 x 1770 x 1470mm.				
HP sewer jetting hose	80m. 1/2"(ND13)				80m. 5/8" (ND16)

\* Unlimited choice of effective tank volume: 500 to 900 litres



Hydraulically driven HP reel, 270° rotational, lockable at any angle



Control box / electronics mounted in lockable, vandalism and water-resistant toolbox



Second control panel swinging out with HP reel, mounted at an ergonomic working height



Rotating stainless steel drip tray prevents your machine from becoming dirty



Transparent fuel tank with convenient filling opening



Lockable bonnet with large opening angle – ideal for service/maintenance of the engine/pump compartment

# ROM 900 Detail photos standard model



Design dashboard with pressure gauge



Water filter (PE) with automatic stop valve



Durable, heavy-duty nose stand with automatic folding jockey wheel



Open storage box for hoses



Integrated lighting units protected in the bumper



Support legs – extra security for hydraulic reeling of the HP hose



Bonnet catch with unlocking handle in the toolbox



Minimum valve wear due to the unique 2x2 hydraulically operated pressure on/off system



Polyethylene water tank cover with snap-lock seal



ROM sewer jetting hose in 1/2" version  
(up to 120m. possible)



Galvanised filling hose reel with 50m. 3/4" filling hose



Impact-resistant covers and bottom panels  
– scratches and tears are easy to repair



Infinitely adjustable pressure regulator  
mounted at a least frost-sensitive position



Two large, lockable toolboxes



Reliable engine temperature management  
by means of a heat exchanger



Maximum fuel savings due to minimum  
drag



Fully hot dip galvanised  
chassis



Maintenance-free battery integrated in  
frame under toolbox

# ROM 900 Options



Light alloy wheels



Remote control Professional Yellow



Fixed ventury-type ejector for filling the tank with surface water



ROM Pulsation system



ROM 900 in your own company- or municipality colour



Storz coupling



Working light with magnetic bracket



Rotating beacon on telescopic pole



Extra tank for anti-freeze suction

- 15" light alloy wheels
- Remote control Professional Yellow (7- or 11-channel)
- Unreeling via remote control
- Additional remote control unit with 50m. cable reel for use on machines with wireless remote control
- Automatic starting of diesel engine via control box and remote control
- 2nd HP reel instead of the filling reel. With ROM 3-way/unloader combination system
- Fixed ventury-type ejector incl. 10m. hose and strainer basket; for filling the tank from surface water (mounted at the reels, least frost-sensitive position)
- Dry run protection
- ROM Pulsation system; applicable in many ways
- Oil spillage control unit with narrow / wide track spraying booms and solvent tank
- Trolley with reel and special hp-hose for drainage cleaning
- Special color for unit (RAL)
- Storz coupling including 2" plug. Mounted at reels, least frost-sensitive position
- Adjustment of tankcapacity to max. towing capacity of vehicule (500 to 900 litres)
- Working light on magnetic bracket
- Rotating beacon on telescopic pole
- Extra tank for anti-freeze suction
- 90m. instead of 80m. 5/8" HP sewer cleaning hose
- 120m. instead of 80m. 1/2" HP sewer cleaning hose
- 40m. 3/8" HP steelply hose, incl. ROM jetting nozzle 32 and grenade 42
- 40m. 3/8" HP steelply hose, incl. quick-release joint for the spraygun/lance
- Bypass switch for dry-run protection
- Nozzle storage rack, mounted inside toolbox



# ROM bv



Harselaarseweg 63  
3771 MA Barneveld, Holland

Phone : +31 (0)342 49 04 17  
Fax : +31 (0)342 49 28 00

E-mail : info@rombv.com  
Internet : www.rombv.com

