

ROM 300/400 SEWER JETTING TRAILER

ROM
KOKS GROUP



ROM 300/400

The ROM 300/400 trailer is a professional sewer cleaning machine for unblocking and cleaning house connections in the sanitary sewer system of up to Ø300mm.

The trailer is equipped with a galvanised undercarriage and an integrated brake system. The low weight of the unit makes the trailer suitable for towing behind almost any vehicle. The application of a specially developed noise-insulation package makes the machine very quiet.

Owners of ROM trailers include municipalities and specialised sewer cleaning companies. Even though the standard package ROM 300/400 trailer is very complete, there are a large number of options and accessories available.



TYPICAL ROM 300/400 CHARACTERISTICS

NOISE REDUCTION

Low noise level achieved through a specially developed noise-insulation package.

WEIGHT DISTRIBUTION

The trailer has a PE water tank positioned lengthwise, establishing a very favourable weight distribution, both with empty and full tank. This results in a very stable and safe roadholding.

REEL

The trailers are standard equipped with one high pressure reel including a 60m 1/2" ROM sewer cleaning hose and one water filling reel with a 50m 3/4" low pressure water hose.

TOOLBOXES

Large, lockable toolboxes are located on both sides of the trailer for the simple and convenient storage of all your materials.

ROM 3-WAY VALVE SYSTEM

Maximum cleaning effect at the nozzle through use of the innovative ROM 3-way valve system with minimal pressure loss. Delivered standard with two nozzles and a spray gun with lance.

CE MARK OF QUALITY

Built by professionals at an ISO-certified company and finished to your specifications. Produced in compliance with the safety requirements demanded for the CE mark of quality.



LEADING IN ALL FIELDS



The ROM 300/400 is available in the following configurations:

Article number	0201	0202	0203	0205
Name	ROM 300 with pump/ engine cover 150/40	ROM 300 without pump/ engine cover 150/40	ROM 400 150/40	ROM 400 140/50
Engine	18hp B&S petrol	18hp B&S petrol	18hp B&S petrol	20hp B&S petrol
Pump	Speck 150 bar - 40l/min	Speck 150 bar - 40l/min	Speck 150 bar - 40l/min	Speck 140 bar - 50l/min
Tank capacity	300l.		450l.	
Empty weight	approx. 450kg	approx. 440kg	approx. 560kg	approx. 560kg
Dimensions l x w x h	3000 x 1500 x 1500mm		3420 x 1500 x 1520mm	
Hose	60m 1/2"			



Options

ROM
KOKS GROUP



Remote control Professional Yellow



Working light with magnetic bracket



Hydraulically driven HP reel incl. hose guiding system



80m 1/2" (ND13) sewer jetting hose instead of 50m



Rotating beacon on extending pole



Oil spillage control unit

- Professional Yellow 7 channel radio remote control
- Extra cable reel with 50m cable for the radio remote control
- Cable remote control system with electric 3-way switching
- Working light with magnetic bracket
- Rotating beacon on extending pole
- Painted in your company- or municipality colour
- Hydraulically driven high pressure reel with optional hose guiding system
- 2nd high pressure reel instead of water filling reel
- Fixed venturi-type ejector for filling the tank with surface water
- Dry run protection
- Special connection for filling with water from a fire hydrant, type Storz
- ROM pulsation system, pulsing force to guide the hose through bends
- Oil spillage control unit, consisting of: wide and narrow track spray boom, separate stainless steel tank for the solution and stainless steel high pressure reel

ROM bv

Harselaarseweg 63
3771 MA Barneveld, Holland

Phone : +31 (0)342 49 04 17
Fax : +31 (0)342 49 28 00

E-mail : info@rombv.com
Internet : www.rombv.com

